

WATER WELL REPORT	Notice of Intent No. WE35718		
Type of Work: State of Washington Construction	Unique Ecology Well ID Tag No. BMG202 Site Well Name (if more than one well):		
☐ Decommission	Water Right Permit/Certificate No.	AHC D	0 2010
Proposed Use: ☑ Domestic ☐ Industrial ☐ Municipal ☐ Dewatering ☐ Irrigation ☐ Test Well ☐ Other	Property Owner Name DON MORSE		
Construction Type: Method:	Well Street Address	Jepartmer	nt of Ecology
⊠ New well □ Alteration □ Driven □ Jetted □ Cable Tool □ Deepening □ Other □ Dug ☒ Air- □ Mud-Rotary	City County EESYENS Washington Office Tax Parcel No. 2568415		
Dimensions: Diameter of boring 6 in., to 100 ft. Depth of completed well 100 ft.	Was a variance approved for this well? Yes	⊠ No	
Construction Details: Wall	If yes, what was the variance for?		
Casing Liner Diameter From To Thickness Steel PVC Welded Thread	Location (see instructions on page 2): □ WWM or ⊠ EWM SE ¼-¼ of the NW ¼; Section 2 Township 32N Range 40E		
in		(Example: 47.12345)	
inininin.	Longitude (Example: 47.12343) Longitude (Example: -120.12345)		
Perforations: ☐ Yes ☒ No Type of perforator used	Driller's Log/Construction or Decommission Procedure		
No. of perforations in. by in. Perforated from ft. to ft. below ground surface Screens: ⊠ Yes □ No □ ⊠ K-Packer □ Depth 93 ft.	Formation: Describe by color, character, size of material and structure, and the kind and nature of the material in each layer penetrated, with at least one entry for each change of information. Use additional sheets if necessary.		
Screens: Yes □ No K-Packer Depth 93 ft. Manufacturer's Name	Material	From	То
Type STAINLESS Model No.	TOP SOIL	0	1
Diameter 5 in. Slot size 10 in. from 95 ft. to 100 ft. Diameter in. Slot size in. from ft. to ft.	FINE SAND	1	2
	FINE SAND AND GRAVEL	2	27
Sand/Filter pack: ☐ Yes ⊠ No Size of pack material	SAND AND BROWN CLAY	27	62
Materials placed from ft. to ft.	SAND AND GRAY CLAY	62	78
Surface Seal: Seal: Yes No To what depth? 18 ft. Material used in seal BENTONITE Did any strata contain unusable water? Yes No Type of water? Depth of strata Method of sealing strata off	SAND AND GRAVEL WWATER	78	100
Pump: Manufacturer's Name			
Water Levels: Land-surface elevation above mean sea levelft. Stick-up of top of well casing 2 ft. above ground surface Static water level 17 ft. below top of well casing Date 7/9/19 Artesian pressure lbs. per square inch Date			
Artesian water is controlled by(cap, valve, etc.)			
Well Tests: Was a pumping test performed? ⊠ No ☐ Yes ➡ by whom? Yield gpm with ft. drawdown after hrs.			
Yield gpm with ft. drawdown after hrs. Yield gpm with ft. drawdown after hrs.			
Recovery data (time = zero when pump is turned off – water level measured from well top to water level)			
Time Water Level Time Water Level Time Water Level			
Date of pumping test			
Bailer test gpm with ft. drawdown after hrs. Air test 20 gpm with stem set at 100 ft. for 1 hrs. Date 7/9/19			
Artesian flowgpm Temperature of water° F Was a chemical analysis made? ☐ Yes ⊠ No	Start Date 7/7/19 Completed D	ate <u>7/9/19</u>	
WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept construction standards. Materials used and the information reported above are tr	esponsibility for construction of this well, and its com		Washington well
☑ Driller ☐ Trainee ☐ PE Print Name SAM BEARDSLEE	Drilling Company BEARDSLEE DRILLING	3	
Signature	Address 4090E. ASTOR		
License No. 2905	City, State, Zip COLVILLE, WA 99114		
IF TRAINEE: Sponsor's License No.	-		
Sponsor's Signature	Contractor's Registration No. BEARDDL818MA 7/1/21		Date