WE25124

WATER WELL REPORT

Construction Conditions Notice W046972 OWNER: CRIST, CAVID OWNER BIO SOUTH CHESTER STREET COLVILLE, WA 99114 Well Add 842-U VALLEY WESTSIDE RD City: Colville, WA 99114 Well Add 842-U VALLEY W	State of Washington Date Printed: 05-Oct-2017 Log No.	Unique Ecology Well I.D. No AAK007
ONNER ADD 819 SOUTH CHESTER STREET COLVILLE, WA 99114 Velid Add 82-U VALLEY WESTSIDE RD CICLY, Colville, WA 99114 Velid Add 82-U VALLEY WESTSIDE RD CICLY, Colville, WA 99114 Velid Add 82-U VALLEY WESTSIDE RD CICLY, Colville, WA 99114 Velid Add 82-U VALLEY WESTSIDE RD CICLY, Colville, WA 99114 Country Stevens Location: SW 1/4 SW 1/4 Sec 20 17 35 R 39E EW Latt. Deap Location: At 1/6 to 290 ft. The ristalladd. PVC A "Dia from 17 ft. to 280 ft. "Dia from ft. to ft. The refrontations: Ves Used In: LINER Perforations: Ves Used In: LINER Perforations from 120 ft. to 280 ft. Perforations from ft. to ft. Perforations ft. Perforations ft. Perforations ft. Perforations ft. Perfo	Construction Notice MAGAZOZO	Water Right Permit Number:
COLVILLE, WA 99114 COUNTY: Country: Stevens Casing installed EXISTING 8 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 59 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 4 * Dia from +1 h. to 50 ft 5 * Dia from +1 h. to 50 ft 5 * Dia from +1 h. to 50 ft 5 * Dia from +1 h. to 50 ft 6 * Dia from +1 h. to 50 ft 7 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 5 * Dia from +1 h. to 50 ft 6 * Dia from +1 h. to 50 ft 7 * Dia from +1 h. to 50 ft 8 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 1 * Dia from +1 h. to 50 ft 2 * Perforations from 120 ft. to 10 ft 2 * Perforations from 150 ft. to 11 ft 2 * Perforations from 150 ft. to 11 ft 2 * Perforations from 150 ft. to 11 ft 3 * Dia from 150 ft. to 11 ft 4 * Dia from +1 h. to 11 ft 5 * Dia from +1 h. to 11 ft 5 * Dia from +1 h. to 11 ft 5 * Dia from +1 h. to 50 ft 5 * Dia from +1 h. to 50 ft 6 * Dia from +1 h. to 50 ft 6 * Dia from +1 h. to 50 ft 7 * Dia from +1 h. to 50 ft 8 * Dia from +1 h. to 50 ft 8 * Dia from +1 h. to 50 ft 8 * Dia from +1 h. to 50 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 8 * Dia from +1 h. to 11 ft 9 * Dia from +1 h. to 11 ft 9 * Dia from +1 h. to 11 ft 10 * Dia from +1 h. to 11 ft 10 * Dia from +1 h. to 11 ft 10 * Dia from +1 h. to 11 ft 10 * Dia f	SONSLIGERON	
DEEPEND Method: ROTARY DIMENSIONS: Diameter of well: 6 inches Depth of completed well 280 ft. Depth of completed well 280 ft. Location: \$\text{M1 / M W 1/4 Sec 20 T 35 R 39E EW} DIMENSIONS: Diameter of well: 6 inches Dimited 60 ft. Depth of completed well 280 ft. Location: \$\text{M1 / M W 1/4 Sec 20 T 35 R 39E EW} Dimensional Completed well 280 ft. Location: \$\text{M1 / M W 1/4 Sec 20 T 35 R 39E EW} Location: \$\text{Location: }\text{Location: }\te	PROPOSED USE: DOMESTIC	
DIMENSIONS: Diameter of well: 6 inches	YPE OF WORK: Owners's Well Number: (If more than one well)	
IMMENSIONS: Diameter of well: 6 inches Joiled 60 ft. Depth of completed well 280 ft. Liner installed: PVC 4 "Dia from 17 ft. to 280 ft. "Dia from ft. to ft. "Dia from ft. to	DEEPENED Method: ROTARY	
Construction Details: Casing installed EXISTING 6 "Dia from +fit to 59 ft 1" Dia from ft to ft 1" Dia ft 1" Di		
Construction Details: Liner installed: PVC 4 "Dia from #1 ft. to 59 ft "Dia from #1 ft. to 50 ft "Dia from #1 ft. to 59 ft "Dia from #1 ft. to 60 ft. to 50 ft. t		Lat/Long: Lat Deg Lat Min/Sec
Liner installed: PVC 4 "Dia from 17 ft. to 280 ft. "Dia from ft. to ft. "Deforations from ft. to ft. "Dia ft. to 280 ft. "Deforations from ft. to ft. "Dia ft. to 50 ft. "Dia	ONSTRUCTION DETAILS: Casing installed EXISTING	1 N
4 "Dia from 17 ft. to 280 ft. "Dia from ft. to ft Perforations: Yes Used In: LINER 'yee of perforations: Yes Used In: LINER 'yee of perforations and the line of the material in each stratum poneration. Despite by polar, Characteric 380 of manufacture of the material in each stratum poneration. Despite by polar, Characteric 380 of manufacture of the material in each stratum ponerated. Show at least one entry for each change in formation. Material Security of the entry for each change in formation. Material Perforations from 120 ft. to 280 ft. Perforations from 120 ft. to 16. Security is not stratum. Perforations from 150 ft. to 16. Security is not stratum. Perforations from 150 ft. to 16. Security is not stratum. Stock stratum is not size: from 16. to 16. Sealing stratum of the stratum is not size: from 16. to 16. Sealing stratum of the stratum of the seal method: Material used in seal EXISTING bid any strata contain unusable water. No Depth of strata bethod of sealing strata off PPUMP: Manufacture's name yee. H.P. 0 WATER LEVELS Land-surface elevation above mean sea level: 0 ft. Istatic level 95 ft. below top of well Date 08/24/2016 with stain pressure. Its per square inch Date Water Level 1 mile: Water Level galmin with 16 ft drawdown after liefeld: galmin with 16	6 " Dia from +1 ft. to 59 ft.	negonies,
Perforations: Yes Used in: LINER ype of perforation styles in. by 7 in. 20 Perforations from 120 ft. to 280 ft. Perforations from 120 ft. to 280 ft. Perforations from 120 ft. to 150 ft. Perforations from 150 ft. Perfora	Did Holli II. to II.	ACAMOTEMATICAL OR RECOMMISSION PROCEDURE
prope of perforator used SKILL SAW IZE of perforations 1/8 in. by 7 in. IZE of perforations from 1.0 ft. to 280 ft. Perforations from ft. to ft. Perforations from ft. to ft. Perforations from ft. to ft. Screens: 0 K-Pac Location: Manufacture's Name Vipe: Model No Diam. slot size: from ft. to ft. Department of Ecology Notes: Eastern Washington Offic9 Work slate orations and washington Offic9 Work slate of saling strat off Well. CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Work slate of saling strat off Well. CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Work slate galleria with ft. ft. drawdown after level measured from well and slate oration and slate slate slate in ft. washington Offic9 Washington oration and slate slate slate slate in ft. slate of text slate of text slate or ft. slate or ft. slate or ft. slate or ft. slat	4 Dia from 17 ft. to 280 ft. "Dia from ft. to ft.	
ype of perforations 1/8 in. by 7 in. 20	Coca III. —III.	
Perforations from 120 ft. to 280 ft. Perforations from from ft. to ft. Perforations from from ft. to ft. Perforations from ft. to ft. Screens: 0 K-Pac Location: danufacture's Name Vype: Model No Diam. slot size: from ft. to ft. D	Type of perforator used SKILL SAW	perietrated. Show at least one entry for each orange in formation.
Perforations from ft. to ft. Sae GRANITE BROKEN W/WATER 12 GPM 220 245 Sae GRANITE MED 245 255 Sae GRANITE MAD 245 255 Sae GRANITE MED 245 255 Sae GRANITE MED 245 255 Sae GRANITE MED 245 255 Sae GRANITE MAD 255 Sae GRANITE MED 255 Sae GRANITE MAD 255 Sae GRANITE MED 25	M	2 CONTROL S
Perforations from ft. to ft. Screens: 0 K-Pac Location: Janufacture's Name John Sidt size: from ft. to ft. John Sidt size:		
Screens: 0 K-Pac Location: Janufacture's Name Type: Model No Joim. slot size: from ft. to ft. Join. Size of Gravel Adetriad placed fro ft. to ft. Join. Size of Gravel Adetriad placed fro ft. to ft. Join. Size of Gravel Adetriad size of forward size of ft. Join. Size of Gravel Adetriad size of ft. Join. Size of Gravel Adetriad of sealing strata off PuMP: Manufacture's name Joye: H.P. 0 NATER LEVELS Land-surface elevation above mean sea levei: 0 ft. Join. Size of Gravel Adetriad of sealing strata off PuMP: Manufacture's name Joye: H.P. 0 NATER LEVELS Land-surface elevation above mean sea levei: 0 ft. Join. Size of Gravel Adetriad of sealing strata off Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 We	7 (2000)	
Screens: 0		
Type: Model No Diam. slot size: from ft. to ft. Diam. slot size: sastem Washington Office WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220,		
Jaim. slot size: from fit. to fit. Jurface seal: No To what depth fit. Depariment of Ecology Notes: Eastern Washington Office WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 WELL CAVED IN @ 195 - 220,	7.7.1.2.20	
Size of Gravel / Filter packed: No Size of Gravel / Alaterial placed fro ft. to ft. Surface seal: No To what depth ft. Seal method: Material used in seal EXISTING Sold any strata contain unusable water No Depth of strata / Method of sealing strata off PUMP: Manufacture's name / Ype: H.P. 0		
Stravel/Filter packed: No Size of Gravel Atterial placed fro ft. to ft. Surface seal: No To what depth ft. Sold any strata contain unusable water No Depth of strata Method of sealing strata contain unusable water No Type of water Depth of strata More and the strata off PUMP: Manufacture's name PUMP: Manufacture's name PUMP: Manufacture's name PUMP: Manufacture's name PUMP: More and the strata off PUMP: More and the strata off WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Work starte 08/23/2016 Complete 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Static level 95 ft. below top of well Date 08/24/2016 Introduced and the information reported are from well politowing the politowing t		KEGEIVED
Material placed fro ft. to ft. Surface seal: No To what depth ft. Department of Ecology Notes: Eastern Washington Office Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN		
Autrace seal: No To what depth ft. Department of Ecology Notes: Eastern Washington Office Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM	and the state of t	OCT 17 2017
Department of Coolings Seal method: Material used in seal EXISTING Did any strata contain unusable water No Depth of strata No Depth of strata No Depth of sealing strata off		·
Notes: Eastern Veashington Onices Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Well CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Work starte 08/23/2016	Tarias Coar. 110	Department of Ecology
WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Water Depth of strata WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220 Water Level strata off Water Level S		Notes: Eastern Washington Office
### Additional of sealing strata off PUMP: Manufacture's name		WELL CAVED IN @ 195 - 220, AIRTESTED @ 6 GPM AT 220
Work starte 08/23/2016 Complete 08/24/2016 WATER LEVELS Land-surface elevation above mean sea level: 0 ft. Static level 95 ft. below top of well Date 08/24/2016 Intesian Pressure los per square inch Date of the information reported are true to my best knowledge and belief. WELL TESTS: Drawdown is amount water level is lowered below static level. Was a pump test made No If yes, by whom lield: gal/min with ft drawdown after lield: gal/min with gal/min with ft drawdown after lield: gal/min with gal/min wit	Method of sealing strata off	
WATER LEVELS Land-surface elevation above mean sea level: Office the static level 95 ft. below top of well Date 08/24/2016 Interest of the static level 95 ft. below top of well Date 08/24/2016 Interest of the static level 95 ft. below top of well Date 08/24/2016 Interest of the static level 95 ft. below top of well Date 08/24/2016 Interest of the static level 95 ft. below top of well Date 08/24/2016 Interest of the static level 15 below top of well Date 08/24/2016 Interest of the static level 15 below top of well Date 08/24/2016 Interest 12 gal/min w/stem set at 279 ft. for 1 1/2 hours reteal and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction standards. Materials used and the information reported are true to my best knowledge and belief. I constructed and/or accept responsibility for construction standards. Alterials Washington well construction standards. In constructed and/or accept re	PUMP: Manufacture's name	
Constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally all Washington well construction standards. Materials used and the information reported are functionally all washington well con	ype: H.P. 0	Work starte 08/23/2016 Complete 08/24/2016
Constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well constructed and/or accept responsibility for construction of this well and its compliance with all Washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally with all Washington well construction standards. Materials used and the information reported are functionally all Washington well construction standards. Materials used and the information reported are functionally all washington well con	NATER LEVELS Land-surface elevation above mean sea level: 0 ff	WELL CONSTRUCTION CERTIFICATION:
Artesian Pressure Ibs per square inch Date Artesian water controlled by WELL TESTS: Drawdown is amount water level is lowered below static level. Was a pump test made No If yes, by whom Vield: gal/min with ft drawdown after	2 250	I constructed and/or accept responsibility for construction of this well and its compliance with
Artesian water controlled by WELL TESTS: Drawdown is amount water level is lowered below static level. Was a pump test made No If yes, by whom field: gal/min with ft drawdown after field: gal/min with ft drawdown after field: gal/min with ft drawdown after field: gal/min ft drawdown after field: gal/min with f	AND CONTRACTOR OF TAXABLE STATE OF TA	
Vas a pump test made No If yes, by whom Signature	Artesian Pressure los per square inchi Date Artesian water controlled by	☑ Driller ☐ Engineer ☐ Trainee
field: gal/min with	VELL TESTS: Drawdown is amount water level is lowered below static level.	Name: JON RICARD License No.: 2341
field: gal/min with ft drawdown after ft drawdown after gal/min with ft drawdown after gal/min with ft drawdown after ft drawdown after gal/min with ft drawdown after gal/min with ft drawdown after gal/min with ft drawdown after gal/min ft drawdown after ft drawdown after gal/min ft drawdown after hrs. fir test 12 gal/min w/ stem set at 279 ft. for 1 1/2 hours resian flow gpm Date If trainee, Licensed driller is: License No.: Licensed Driller Signature	Vas a pump test made No If yes, by whom	Signature: SeMureur
Secovery data (time taken as zero when pump turned off) (water level measured from well op to water level Drilling Company:	'ield: gal/min with ft drawdown after	If trained Licensed driller is: License No :
Drilling Company: NAME: FOGLE PUMP & SUPPLY, INC. Shop: COLVILLE ADDRESS: 2250 NORTH HWY Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com fax: 12 gal/min w/ stem set at 279 ft. for 1 1/2 hours resian flow gpm Date Drilling Company: NAME: FOGLE PUMP & SUPPLY, INC. Shop: COLVILLE ADDRESS: 2250 NORTH HWY Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's	ield: gal/min with ft drawdown after	License vincins.
prior to water level Fime: Water Level Time: Water Level ADDRESS: 2250 NORTH HWY Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		Licensed Driller Signature
NAME: FOGLE PUMP & SUPPLY, INC. Shop: COLVILLE ADDRESS: 2250 NORTH HWY Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com fit drawdown after hrs. ir test 12 gal/min w/ stem set at 279 ft. for 1 1/2 hours rtesian flow gpm Date NAME: FOGLE PUMP & SUPPLY, INC. Shop: COLVILLE ADDRESS: 2250 NORTH HWY Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		Drilling Company:
Colville, WA 99114 Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		NAME: FOGLE PUMP & SUPPLY, INC. Shop: COLVILLE
Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		ADDRESS: 2250 NORTH HWY
Phone: 509-684-2569 Toll Free: 800-533-6518 E-Mail: jeanne@foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		Colville, WA 99114
arte of test: 8/24/2016 Failer test gal/min ft drawdown after hrs. FAX: 509-684-3032 WEB Site: www.foglepump.com FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
ir test 12 gal/min w/ stem set at 279 ft. for 1 1/2 hours rtesian flow gpm Date FAX: 509-684-3032 WEB Site: www.foglepump.com Contractor's		E-Mail: jeanne@foglepump.com
rtesian flow gpm Date Contractor's		
Contractors		

CURRENT

Notice of Intent No.: