

220422



△ NORTHWEST CORNER SECTION IS ~ ROUND 3/4" DIAMETER, DEEPS 6" SET BY B.L.M. IN 1763. FOUND ROCK LIVING. B.T.'S: A 12" R. DEEPS 3" UP W. 2.5 FT. A 13" R. DEEPS 3" UP W. 14.5 FT.; AN 8" CR. DEEPS 18" DEEP E. 40.0 FT.; AN 10" CR. DEEPS 51.5 3/4" W. 59.1 FT. AS PER RECORD.

▲ NORTH QUARTER CORNER SECTION IS ~ POUND 3/4" DIAMETER BEAR5 CAP SET BY B.L.M. IN 1963. FOUND TWO LIVING B.T.S.: A 1 1/2" FIR BEAR5 50% E, 25.0 FT.; AL50, A 2 1/4" FIR BEAR5 N 55 1/2° E, 17.6 FT.

▲ NORTHEAST CORNER SECTION IS ~ ROUND 3 1/4" DIAMETER BEARS CAP SET BY S.L.M. IN 1963. FOUND NEE LIVING BT. A 26" FIR BEARS 5 32 1/4" W. 66.7 FT. A 16" PINE BEARS N 89 3/4" E. 60.0 FT. ALSO, A 16" FIR BEARS 5 74 1/2" E. 48.8 FT.

A EAST QUARTER CORNER SECTION IS ~ ROUND 3 IN BEARS CAP SET BY B.M. IN 1963. FOUND TWO LIVING BT'S: A 14" FIR BEARD N 56 1/2° E, 70.6% ALSO, A 24" FIE BEARD S 26 1/2° W, 54.8 FT. AS PER RECORD.

△ SOUTH QUARTER CORNER SECTION 15 ~ ORIGINAL RECORD OF SUEVEY, SECTION 22.

A SOUTHWEST CORNER SECTION IS ~ ORIGINAL STONE MONUMENT. SEE CORNER NOTES FOR NW RECORDED OF SURVEY, SECTION 21.

WEST QUARTER CORNER SECTION 15 - FOUND
94" x 22" x 6" BOULDER IN PLACE AS PER C.L.O.
SURVEY RECORDED. REMAINS OF FALLEN 16"

FINE PLANKS AND BEAMS
HOLE WITH REMAINS OF A 30" FINE BEAMS
5643/4"W, 91.7 FT (C.L.O 159) SET TWO
NEW D.T.B, A 22" FIR BEAMS N 59°W, 21.9 FT,
ALSO, A 12" FIR BEAMS N 77°E, 29.5 FT.

Q2

200122

AUDITOR'S CERTIFICATE

Seeance 1965 at 139 in book 2
of surveys at page 23 at the
request of Grant Tolton.

CLARENCE H. COOK, COUNTY AUDITOR

THIS MAP CORRECTLY REPRESENTS
A SURVEY MADE BY ME OR UNDER
MY DIRECTION IN CONFORMANCE

WITH THE REQUIREMENTS OF THE
SURVEY RECORD ACT AT THE
REQUEST OF ROY LELAND.

CERTIFICATE NO. 20865

BOUNDARY SURVEY FOR:



LELAND COMPANY
WEST 1520 5th AVE. SPOKANE, WASH. 99204

MID-MOUNTAIN SURVEYORS
PROFESSIONAL LAND SURVEYORS
P.O. BOX 275

CURLEW, WASHINGTON 99118